

inédit
LIGHTING


200CENT ROUND 250LM SWING 90 TRIM IP54

BATHROOM - SALLE DE BAINS

Adjustable 0° - 90°

Ø27 mm - h = 70 mm

Material: Aluminium



200CENT ROUND SWING 90 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 553 27 530	REF N° 553 27 930	REF N° 553 27 830	REF N° 553 27 730

3 W - 250LM - 2 step MacAdam - **A+**
Serial wiring - - - -
Requires remote LED driver - 1050mA
Standard narrowbeam 12° - Optional 8° beam
Ultra low glare (UGR < 13)

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - - IP20 - 1050mA - not dimmable



REMOTE LED DRIVER DIM

REF N° 697 60 025 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 70 050 min 2W max 45W PHASE DIM

230V/50Hz - - current controlled
 - - IP20 - 1050mA - dimmable



INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø 27 mm



BEAM ANGLES

STANDARD (included) beam angle 12°
REF N° 203 20 008 (option) beam angle 8°


200CENT ROUND 500LM SWING 90 TRIM IP54

BATHROOM - SALLE DE BAINS

Adjustable 0° - 90°

Ø27 mm - h = 70 mm

Material: Aluminium



200CENT ROUND SWING 90 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 553 28 530	REF N° 553 28 930	REF N° 553 28 830	REF N° 553 28 730

5,9 W - 500LM - 2 step MacAdam - **A+**
Serial wiring - - **CE** - -
Requires remote LED driver - 700mA
Standard Perfectbeam 24° - Optional 44° beam
Ultra low glare (UGR < 13)

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - **CE** - IP20 - 700mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W

1-10V DALI PUSH



REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 77 010 min 2W max 10W PHASE DIM

REF N° 697 77 020 min 11W max 20W PHASE DIM

230V/50Hz - - current controlled
 - **CE** - IP20 - 700mA - dimmable



INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø 27 mm



BEAM ANGLES

STANDARD (included) beam angle 24°
REF N° 203 20 044 (option) beam angle 44°

inédit
LIGHTING


200CENT ROUND 750LM SWING 90 TRIM IP54

BATHROOM - SALLE DE BAINS

Adjustable 0° - 90°

Ø27 mm - h = 70 mm

Material: Aluminium



200CENT ROUND SWING 90 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 553 29 530	REF N° 553 29 930	REF N° 553 29 830	REF N° 553 29 730

6,2 W - 750LM - 2 step MacAdam - **A+**
Serial wiring - - - -
Requires remote LED driver - 250mA
Standard beam angle 36°

REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.2W max. 30W

REF N° 697 00 080 min.27W max. 67W

230V/50Hz - - current controlled
 - - IP20 - 250mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 30W



1-10V DALI PUSH

REF N° 697 30 070 min 33W max 65W DALI

REF N° 697 60 080 min 27W max 67W 1-10V PUSH

REF N° 697 72 020 min 6W max 12,5W PHASE DIM

230V/50Hz - - current controlled
 - - IP20 - 250mA - dimmable



INSTALLATION KIT

REF N° 680 01 027 standard holesaw Ø 27 mm



BEAM ANGLES

STANDARD (included) beam angle 36°