


200CENT ROUND 250LM ADJ TRIMLESS IP20

INDOOR - INTÉRIEUR



Adjustable 0° - 25°

114x134 mm - h = 100 mm

Material: CALCYT® plaster



Max angle 25°



Ref N° 200 BL CR



Black Chrome - Nero Cromo
Schwarz Chrom - Zwart Chroom
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

Chiedere una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

200CENT ROUND ADJ IP20 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 530 27 530	REF N° 530 27 930	REF N° 530 27 830	REF N° 530 27 730

3 W - 250LM - 2 step MacAdam - **A+**
Serial wiring - - - -
Requires remote LED driver - 1050mA
Standard narrowbeam 12° - Optional 8° beam
Ultra low glare (UGR < 13)

Ref N° 200 BL BL



Black Black - Nero Nero
Schwarz Schwarz - Zwart Zwart
Noir Noir - Negro Negro

Ref N° 200 WH BL



White Black - Bianco Nero
Weiß Schwarz - Wit Zwart
Blanc Noir - Bianco Negro

Ref N° 200 BL WH



Black White - Nero Bianco
Schwarz Weiß - Zwart Wit
Noir Blanc - Negro Bianco

Ref N° 200 WH WH



White White - Bianco Bianco
Weiß Weiß - Wit Wit
Blanc Blanc - Bianco Bianco

REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled
 - - IP20 - 1050mA - not dimmable

Ref N° 200 BL GO



Black Gold - Nero Oro
Schwarz Gold - Zwart Goud
Noir Or - Negro Oro

Ref N° 200 WH GO



White Gold - Bianco Oro
Weiß Gold - Wit Goud
Blanc Or - Bianco Oro

REMOTE LED DRIVER DIM

REF N° 697 60 025 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 70 050 min 2W max 45W PHASE DIM

230V/50Hz - - current controlled
 - - IP20 - 1050mA - dimmable

Ref N° 200 BL CO



Black Copper - Nero Rame
Schwarz Kupfer - Zwart Koper
Noir Cuivre - Negro Cobre

Ref N° 200 WH CO



White Copper - Bianco Rame
Weiß Kupfer - Wit Koper
Blanc Cuivre - Bianco Cobre


INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 12°
REF N° 203 20 008 (option) beam angle 8°


200CENT ROUND 500LM ADJ TRIMLESS IP20

INDOOR - INTÉRIEUR



Adjustable 0° - 25°

114x134 mm - h = 100 mm

Material: CALCYT® plaster



Max angle 25°




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 24°

REF N° 203 20 044 (option) beam angle 44°

Ref N° 200 BL CR



Black Chrome - Nero Cromo
Schwarz Chrom - Zwart Chroom
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

Chiedere una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

200CENT ROUND ADJ IP20 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 530 28 530	REF N° 530 28 930	REF N° 530 28 830	REF N° 530 28 730

5,9 W - 500LM - 2 step MacAdam - **A+**

Serial wiring - - - -

Requires remote LED driver - 700mA

Standard Perfectbeam 24° - Optional 44° beam

Ultra low glare (UGR < 13)

Ref N° 200 BL BL



Black Black - Nero Nero
Schwarz Schwarz - Zwart Zwart
Noir Noir - Negro Negro

Ref N° 200 WH BL



White Black - Bianco Nero
Weiß Schwarz - Wit Zwart
Blanc Noir - Bianco Negro

Ref N° 200 BL WH



Black White - Nero Bianco
Schwarz Weiß - Zwart Wit
Noir Blanc - Negro Bianco

Ref N° 200 WH WH



White White - Bianco Bianco
Weiß Weiß - Wit Wit
Blanc Blanc - Bianco Bianco

REMOTE LED DRIVER ON/OFF


REF N° 697 00 015 min.2W max. 32W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled

- - IP20 - 700mA - not dimmable

Ref N° 200 BL GO



Black Gold - Nero Oro
Schwarz Gold - Zwart Goud
Noir Or - Negro Oro

Ref N° 200 WH GO



White Gold - Bianco Oro
Weiß Gold - Wit Goud
Blanc Or - Bianco Oro

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH


REF N° 697 77 010 min 2W max 10W PHASE DIM

REF N° 697 77 020 min 11W max 20W PHASE DIM

230V/50Hz - - current controlled

- - IP20 - 700mA - dimmable

Ref N° 200 BL CO



Black Copper - Nero Rame
Schwarz Kupfer - Zwart Koper
Noir Cuivre - Negro Cobre

Ref N° 200 WH CO



White Copper - Bianco Rame
Weiß Kupfer - Wit Koper
Blanc Cuivre - Bianco Cobre

200CENT ROUND 750LM ADJ TRIMLESS IP20

INDOOR - INTÉRIEUR

Adjustable 0° - 25°

114x134 mm - h = 100 mm

Material: CALCYT® plaster

Ref N° 200 BL CR



Black Chrome - Nero Cromo
Schwarz Chrom - Zwart Chrom
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

Chiedere una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

Ref N° 200 BL BL



Black Black - Nero Nero
Schwarz Schwarz - Zwart Zwart
Noir Noir - Negro Negro

Ref N° 200 WH BL



White Black - Bianco Nero
Weiß Schwarz - Wit Zwart
Blanc Noir - Bianco Negro

Ref N° 200 BL WH



Black White - Nero Bianco
Schwarz Weiß - Zwart Wit
Noir Blanc - Negro Bianco

Ref N° 200 WH WH



White White - Bianco Bianco
Weiß Weiß - Wit Wit
Blanc Blanc - Bianco Bianco

Ref N° 200 BL GO



Black Gold - Nero Oro
Schwarz Gold - Zwart Goud
Noir Or - Negro Oro

Ref N° 200 WH GO



White Gold - Bianco Oro
Weiß Gold - Wit Goud
Blanc Or - Bianco Oro

Ref N° 200 BL CO



Black Copper - Nero Rame
Schwarz Kupfer - Zwart Koper
Noir Cuivre - Negro Cobre

Ref N° 200 WH CO



White Copper - Bianco Rame
Weiß Kupfer - Wit Koper
Blanc Cuivre - Bianco Cobre

200CENT ROUND ADJ IP20 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 530 29 530	REF N° 530 29 930	REF N° 530 29 830	REF N° 530 29 730

6,2 W - 750LM - 2 step MacAdam - **A+**

Serial wiring - - - -

Requires remote LED driver - 250mA

Standard beam angle 36°

REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.2W max. 30W

REF N° 697 00 080 min.27W max. 67W

230V/50Hz - - current controlled

- - IP20 - 250mA - not dimmable

REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 30W

1-10V DALI PUSH


REF N° 697 30 070 min 33W max 65W DALI

REF N° 697 60 080 min 27W max 67W 1-10V PUSH



REF N° 697 72 020 min 6W max 12,5W PHASE DIM

230V/50Hz - - current controlled

- - IP20 - 250mA - dimmable



Max angle 25°




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 200 99 025 installation system for gypsum ceiling 25 mm

REF N° 200 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box 200Cent - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°