

**inédit**  
LIGHTING

## 200CENT ROUND 250LM LOW TRIM IP54

BATHROOM - SALLE DE BAINS

Fix (not adjustable) 0° - 0°

Ø43 mm - h = 49 mm

Material: Aluminium

### Ref N° 200 BL CR



Black Chrome - Nero Cromo  
Schwarz Chrom - Zwart Chrom  
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

*Chiedere una soluzione personalizzata con il vostro colore RAL preferito*

*Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe*

*Vraag om een niet standaard afwerking of je favoriete RAL kleur*

Demandez une solution sur mesure ou votre couleur RAL préférée

*Solicite una solución a medida o su color favorito de la carta RAL*

### 200CENT ROUND LOW IP54 TRIM 250LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 519 27 531	REF N° 519 27 931	REF N° 519 27 831	REF N° 519 27 731

3 W - 250LM - 2 step MacAdam - **A+**

Serial wiring - - **CE** - -

Requires remote LED driver - 1050mA

Standard narrowbeam 12° - Optional 8° beam

Ultra low glare (UGR < 13)

### Ref N° 200 BL BL



Black Black - Nero Nero  
Schwarz Schwarz - Zwart Zwart  
Noir Noir - Negro Negro

### Ref N° 200 WH BL



White Black - Bianco Nero  
Weiß Schwarz - Wit Zwart  
Blanc Noir - Bianco Negro

### Ref N° 200 BL WH



Black White - Nero Bianco  
Schwarz Weiß - Zwart Wit  
Noir Blanc - Negro Bianco

### Ref N° 200 WH WH



White White - Bianco Bianco  
Weiß Weiß - Wit Wit  
Blanc Blanc - Bianco Bianco

### Ref N° 200 BL GO



Black Gold - Nero Oro  
Schwarz Gold - Zwart Goud  
Noir Or - Negro Oro

### Ref N° 200 WH GO



White Gold - Bianco Oro  
Weiß Gold - Wit Goud  
Blanc Or - Bianco Oro

### Ref N° 200 BL CO



Black Copper - Nero Rame  
Schwarz Kupfer - Zwart Koper  
Noir Cuivre - Negro Cobre

### Ref N° 200 WH CO



White Copper - Bianco Rame  
Weiß Kupfer - Wit Koper  
Blanc Cuivre - Blanco Cobre

### INTEGRAL LED DRIVER

REF N° 697 61 015 15W DIM 1-10V Ø40 x 149mm

REF N° 697 31 015 15W DIM DALI Ø40 x 149mm

230V/50Hz - - **CE** - IP20 - 1050mA  
fits through the opening of Ø43mm

### REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 39W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled  
**CE** - IP20 - 1050mA - not dimmable





### REMOTE LED DRIVER DIM

REF N° 697 60 025 min.3W max. 60W

1-10V DALI PUSH

REF N° 697 70 050 min 2W max 45W PHASE DIM

230V/50Hz - - current controlled  
**CE** - IP20 - 1050mA - dimmable



### INSTALLATION KIT

REF N° 680 01 043 standard holesaw Ø 43 mm



### BEAM ANGLES

**STANDARD** (included) beam angle 12°  
REF N° 203 20 008 (option) beam angle 8°

## 200CENT ROUND 500LM LOW TRIM IP54

BATHROOM - SALLE DE BAINS

Fix (not adjustable) 0° - 0°

Ø43 mm - h = 49 mm

Material: Aluminium

### Ref N° 200 BL CR



Black Chrome - Nero Cromo  
Schwarz Chrom - Zwart Chrom  
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

Chiedete una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

### Ref N° 200 BL BL



Black Black - Nero Nero  
Schwarz Schwarz - Zwart Zwart  
Noir Noir - Negro Negro

### Ref N° 200 WH BL



White Black - Bianco Nero  
Weiß Schwarz - Wit Zwart  
Blanc Noir - Bianco Negro

### Ref N° 200 BL WH



Black White - Nero Bianco  
Schwarz Weiß - Zwart Wit  
Noir Blanc - Negro Bianco

### Ref N° 200 WH WH



White White - Bianco Bianco  
Weiß Weiß - Wit Wit  
Blanc Blanc - Bianco Bianco

### Ref N° 200 BL GO



Black Gold - Nero Oro  
Schwarz Gold - Zwart Goud  
Noir Or - Negro Oro

### Ref N° 200 WH GO



White Gold - Bianco Oro  
Weiß Gold - Wit Goud  
Blanc Or - Bianco Oro

### Ref N° 200 BL CO



Black Copper - Nero Rame  
Schwarz Kupfer - Zwart Koper  
Noir Cuivre - Negro Cobre

### Ref N° 200 WH CO



White Copper - Bianco Rame  
Weiß Kupfer - Wit Koper  
Blanc Cuivre - Blanco Cobre

### 200CENT ROUND LOW IP54 TRIM 500LM CRI 92

2200°K	2700°K	3000°K	4000°K
REF N° 519 28 531	REF N° 519 28 931	REF N° 519 28 831	REF N° 519 28 731

5,9 W - 500LM - 2 step MacAdam - **A+**  
Serial wiring - - **CE** - -   
Requires remote LED driver - 700mA  
Standard Perfectbeam 24° - Optional 44° beam  
Ultra low glare (UGR < 13)

### INTEGRAL LED DRIVER

REF N° 697 67 015 15W DIM 1-10V Ø40 x 149mm

REF N° 697 37 015 15W DIM DALI Ø40 x 149mm

REF N° 697 77 010 10W PHASE DIM Ø42 x 94mm

230V/50Hz - - - **CE** - IP20 - 700mA  
fits through the opening of Ø43mm

### REMOTE LED DRIVER ON/OFF

REF N° 697 00 015 min.2W max. 32W

REF N° 697 00 025 min.2W max. 50W

230V/50Hz - - current controlled  
 - **CE** - IP20 - 700mA - not dimmable

### REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 60W

1-10V DALI PUSH





REF N° 697 30 015 min 2W max 20W DALI

REF N° 697 60 015 min 2W max 20W 1-10V PUSH

REF N° 697 77 010 min 2W max 10W PHASE DIM


REF N° 697 77 020 min 11W max 20W PHASE DIM

230V/50Hz - - current controlled  
 - **CE** - IP20 - 700mA - dimmable



### INSTALLATION KIT

REF N° 680 01 043 standard holesaw Ø 43 mm



### BEAM ANGLES

**STANDARD** (included) beam angle 24°  
REF N° 203 20 044 (option) beam angle 44°

inédit  
LIGHTING

## 200CENT ROUND 750LM LOW TRIM IP54

BATHROOM - SALLE DE BAINS

Fix (not adjustable) 0° - 0°

Ø43 mm - h = 49 mm

Material: Aluminium

Ref N° 200 BL CR



Black Chrome - Nero Cromo  
Schwarz Chrom - Zwart Chrom  
Noir Chrome - Negro Cromo

Ask for a bespoke solution or your favorite RAL color

Chiedete una soluzione personalizzata con il vostro colore RAL preferito

Fragen Sie nach einer individuellen Lösung oder Ihrer Lieblings-RAL-Farbe

Vraag om een niet-standaard afwerking of je favoriete RAL kleur

Demandez une solution sur mesure ou votre couleur RAL préférée

Solicite una solución a medida o su color favorito de la carta RAL

Ref N° 200 BL BL



Black Black - Nero Nero  
Schwarz Schwarz - Zwart Zwart  
Noir Noir - Negro Negro

Ref N° 200 WH BL



White Black - Bianco Nero  
Weiß Schwarz - Wit Zwart  
Blanc Noir - Blanco Negro

Ref N° 200 BL WH



Black White - Nero Bianco  
Schwarz Weiß - Zwart Wit  
Noir Blanc - Negro Bianco

Ref N° 200 WH WH



White White - Bianco Bianco  
Weiß Weiß - Wit Wit  
Blanc Blanc - Blanco Blanco

Ref N° 200 BL GO



Black Gold - Nero Oro  
Schwarz Gold - Zwart Goud  
Noir Or - Negro Oro

Ref N° 200 WH GO



White Gold - Bianco Oro  
Weiß Gold - Wit Goud  
Blanc Or - Blanco Oro

Ref N° 200 BL CO



Black Copper - Nero Rame  
Schwarz Kupfer - Zwart Koper  
Noir Cuivre - Negro Cobre

Ref N° 200 WH CO



White Copper - Bianco Rame  
Weiß Kupfer - Wit Koper  
Blanc Cuivre - Blanco Cobre

### 200CENT ROUND LOW IP54 TRIM 750LM CRI 92

2400°K	2700°K	3000°K	4000°K
REF N° 519 29 531	REF N° 519 29 931	REF N° 519 29 831	REF N° 519 29 731

6,2 W - 750LM - 2 step MacAdam - **A+**  
Serial wiring - - - -   
Requires remote LED driver - 250mA  
Standard beam angle 36°

### INTEGRAL LED DRIVER

REF N° 697 62 015 15W DIM 1-10V Ø40 x 149mm

REF N° 697 32 015 15W DIM DALI Ø40 x 149mm

REF N° 697 70 008 8W PHASE DIM Ø42 x 94mm

230V/50Hz - - - - IP20 - 250mA  
fits through the opening of Ø43mm

### REMOTE LED DRIVER ON/OFF

REF N° 697 00 040 min.2W max. 30W

REF N° 697 00 080 min.27W max. 67W

230V/50Hz - - current controlled  
 - - IP20 - 250mA - not dimmable

### REMOTE LED DRIVER DIM

REF N° 697 60 040 min.3W max. 30W




1-10V DALI PUSH

REF N° 697 30 070 min 33W max 65W DALI

REF N° 697 60 080 min 27W max 67W 1-10V PUSH


REF N° 697 72 020 min 6W max 12,5W PHASE DIM

230V/50Hz - - current controlled  
 - - IP20 - 250mA - dimmable



### INSTALLATION KIT

REF N° 680 01 043 standard holesaw Ø 43 mm



### BEAM ANGLES

STANDARD (included) beam angle 36°