

TECHNICAL DATA SHEET

PIXO 50 FIX IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTERIOR

Fix (not adjustable) 0° - 0°

114x134 mm

Material : CALCYT® plaster

PIXO 50 LED WARMDIM		
WARMDIM : DIMS FROM 3000°K TO 2000°K		
REF N°	500LM CRI80	900LM CRI90
phase DIM	227 72 640	227 73 640
DIM 1-10V	227 62 640	227 63 640
DIM DALI	227 32 640	227 33 640
6 W (500lm) - 12,8 W (900lm) - 4 Step MacAdam		
- 230V/50Hz -  -  -  - 		
Incl. LED driver (phase DIM, 1-10V or DALI)		
Standard beam angle 36° (options 12°, 24°)		
h = 115 mm (500lm) - h = 150 mm (900lm)		

PIXO 50 LED 700LM CRI 80			
REF N°	2700°K	3000°K	4000°K
phaseDIM	227 72 040	227 72 140	227 72 240
DIM 1-10V	227 62 040	227 62 140	227 62 240
DIM DALI	227 32 040	227 32 140	227 32 240

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam
 - 230V/50Hz -  -  -  - 
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 92 mm (phase DIM models beam 36°)
h = 115 mm (all other models)

PIXO 50 HAL	
REF N° 227 10 050	
 QR-CBC 51 - 50W - Gx53 - 12V	
 -  -  - 	
h = 92 mm - exclusive lamp and transfo	

PIXO 50 LED 1300LM CRI 80			
REF N°	2700°K	3000°K	4000°K
phase DIM	227 73 040	227 73 140	227 73 240
DIM 1-10V	227 63 040	227 63 140	227 63 240
DIM DALI	227 33 040	227 33 140	227 33 240

XicatoLED - 11,7W - 1300lm - 2 Step MacAdam

 - 230V/50Hz -  -  -  - 

Incl. LED driver (phase DIM, 1-10V or DALI)


Standard beam angle 36° (options 12°, 24°)

h = 150 mm

PIXO 50 LED 700LM CRI 97			
REF N°	2700°K	3000°K	4000°K
phase DIM	227 72 940	227 72 840	227 72 740
DIM 1-10V	227 62 940	227 62 840	227 62 740
DIM DALI	227 32 940	227 32 840	227 32 740

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam
 - 230V/50Hz -  -  - 
Incl. LED driver (phase DIM, 1-10V or DALI)
Standard beam angle 36° (options 12°, 24°)
h = 115 mm (models beam angle 36°)
h = 150 mm (models beam angle 12° or 24°)

PIXO 50 ES	
REF N° 227 11 050	
 QPAR 16 - 50W - GZ10/GU10 - 	
 - 230V/50Hz -  -  - 	
h = 93 mm - exclusive lamp	




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 261 99 025 installation system for gypsum ceiling 25 mm

REF N° 261 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box Pixo 50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

TECHNICAL DATA SHEET

PIXO 50 ADJUSTABLE IP20

INDOOR - INTERNO - INNENBEREICH - INTERIEUR - INTÉRIEUR - INTERIOR

Adjustable Φ 0° - 30°

114x134 mm

Material : CALCYT® plaster

PIXO 50 LED WARMDIM		
WARMDIM : DIMS FROM 3000°K TO 2000°K		
REF N°	500LM CRI90	900LM CRI90
phase DIM	261 72 640	261 73 640
DIM 1-10V	261 62 640	261 63 640
DIM DALI	261 32 640	261 33 640
6W (500lm) - 12,8W (900lm) - 4 Step MacAdam		
- 230V/50Hz -  -  -  - 		
Incl. LED driver (phase DIM, 1-10V or DALI)		
Standard beam angle 36° (options 24°)		
h = 115 mm (500lm) - h = 150 mm (900lm)		


PIXO 50 LED 700LM CRI 80			
REF N°	2700°K	3000°K	4000°K
phase DIM	261 72 040	261 72 140	261 72 240
DIM 1-10V	261 62 040	261 62 140	261 62 240
DIM DALI	261 32 040	261 32 140	261 32 240
Xicato LED - 5,6 W - 720lm - 2 Step MacAdam			
- 230V/50Hz -  -  -  - 			
Incl. LED driver (phase DIM, 1-10V or DALI)			
Standard beam angle 36° (options 12°, 24°)			
h = 92 mm (phase DIM models beam 36°)			
h = 115 mm (all other models)			

PIXO 50 HAL	
REF N° 261 10 050	
 QR-CBC 51 - 50W - Gx53 - 12V	
 -  -  - 	
h = 92 mm - exclusive lamp and transfo	

PIXO 50 LED 1300LM CRI 80			
REF N°	2700°K	3000°K	4000°K
phase DIM	261 73 040	261 73 140	261 73 240
DIM 1-10V	261 63 040	261 63 140	261 63 240
DIM DALI	261 33 040	261 33 140	261 33 240
Xicato LED - 11,7W - 1300lm - 2 Step MacAdam			
- 230V/50Hz -  -  -  - 			
Incl. LED driver (phase DIM, 1-10V or DALI)			
Standard beam angle 36° (options 12°, 24°)			
h = 150 mm			

PIXO 50 LED 700LM CRI 97			
REF N°	2700°K	3000°K	4000°K
phase DIM	261 72 940	261 72 840	261 72 740
DIM 1-10V	261 62 940	261 62 840	261 62 740
DIM DALI	261 32 940	261 32 840	261 32 740
Xicato LED - 7,4 W - 720lm - 2 Step MacAdam			
- 230V/50Hz -  -  -  - 			
Incl. LED driver (phase DIM, 1-10V or DALI)			
Standard beam angle 36° (options 12°, 24°)			
h = 115 mm (models beam angle 36°)			
h = 150 mm (models beam angle 12° or 24°)			

PIXO 50 ES	
REF N° 261 11 050	
 QPAR 16 - 50W - GZ10/GU10 - 	
 - 230V/50Hz -  -  - 	
h = 93 mm - exclusive lamp	




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 261 99 025 installation system for gypsum ceiling 25 mm

REF N° 261 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box Pixo 50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

TECHNICAL DATA SHEET

PIXO 50 IP54

BATHROOM - STANZA DA BAGNO - BADEZIMMER - BADKAMER - SALLE DE BAINS - CUARTO DE BAÑO

Fix (not adjustable) 0° - 0°

114x134 mm

Material : CALCYT® plaster

PIXO 50 LED WARMDIM

WARMDIM : DIMS FROM 3000°K TO 2000°K

REF N°	500LM CRI80	900LM CRI90
phase DIM	261 72 641	261 73 641
DIM 1-10V	261 62 641	261 63 641
DIM DALI	261 32 641	261 33 641

6W (500lm) - 12,8W (900lm) - 4 Step MacAdam
 - 230V/50Hz -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 24°)
 h = 115 mm (500lm) - h = 150 mm (900lm)

PIXO 50 LED 1300LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	261 73 041	261 73 141	261 73 241
DIM 1-10V	261 63 041	261 63 141	261 63 241
DIM DALI	261 33 041	261 33 141	261 33 241

Xicato LED - 11,7W - 1300lm - 2 Step MacAdam
 - 230V/50Hz -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 150 mm

PIXO 50 LED 700LM CRI 80

REF N°	2700°K	3000°K	4000°K
phase DIM	261 72 041	261 72 141	261 72 241
DIM 1-10V	261 62 041	261 62 141	261 62 241
DIM DALI	261 32 041	261 32 141	261 32 241

Xicato LED - 5,6 W - 720lm - 2 Step MacAdam
 - 230V/50Hz -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 92 mm (phase DIM models beam 36°)
 h = 115 mm (all other models)

PIXO 50 LED 700LM CRI 97

REF N°	2700°K	3000°K	4000°K
phase DIM	261 72 941	261 72 841	261 72 741
DIM 1-10V	261 62 941	261 62 841	261 62 741
DIM DALI	261 32 941	261 32 841	261 32 741

Xicato LED - 7,4 W - 720lm - 2 Step MacAdam
 - 230V/50Hz -  -  - 
 Incl. LED driver (phase DIM, 1-10V or DALI)
 Standard beam angle 36° (options 12°, 24°)
 h = 115 mm (models beam angle 36°)
 h = 150 mm (models beam angle 12° or 24°)

PIXO 50 HAL


REF N° 227 10 051

 QR-CBC 51 - 50W - Gx5,3 - 12V
 -  -  -  - 
 h = 92 mm - exclusive lamp and transfo

PIXO 50 ES

REF N° 227 11 051

 QPAR 16 - 50W - GZ10/GU10 - 
 -  - 230V/50Hz -  -  - 
 h = 93 mm - exclusive lamp




INSTALLATION KIT

STANDARD (included) installation system for ceiling 9 - 12 - 15 mm

REF N° 261 99 025 installation system for gypsum ceiling 25 mm

REF N° 261 99 030 installation system for gypsum ceiling 30 mm

REF N° 827 00 000 Concrete box Pixo 50 - Galvanized steel



BEAM ANGLES

STANDARD (included) beam angle 36°

REF N° 205 50 012 optional beam angle 12°

REF N° 205 50 024 optional beam angle 24°

EMERGENCY UNITS

REF N° 693 01 001 1h basic + control LED

REF N° 693 01 003 3h basic + control LED

REF N° 693 30 001 1h EMPRO DALI

REF N° 693 30 003 3h EMPRO DALI

